

## **Model:DB-600GF**

## Powered by Yuchai



## **Applicable Standards**

- ISO9001
- ISO14001
- ISO45001
- CE

### **Factory Inspection**

- Complete design and quality inspection
- 0%, 25%, 50%, 75%, 100%, 110% load test
- Function test

600KW 750KVA	Diesel Generator Set Specifications
Genset model	DB-600GF
Prime power	600 kW
-	750 kVA
Standby power	660 kW
	825 kVA
Rated voltage(V)	400/230 (customizable)
Rate current(A)	1080 A
Power factor	0.8
Frequency(Hz)	50
Speed(rpm)	1500
Phase:	3 phase 4 wire
Noise level:	105dB at 7m (open type diesel genset)
	75dB at 7m(silent type diesel genset)

#### **Environmental Conditions**

Ambient temperature: +5° C~+40° C

■ Altitude: ≤1000m

Remark: If your conditions are different from the above, please contact our sales.

Туре	Dimensions(mm) L*W*H	Weight(kg)	Base bottom fuel tank (Liter)
Open Type	4500×1750×2100	7200	Without
Silent Type	4900×2200×2600	12000	8 hours

Remark: The dimensions and weight of the above diesel generator set are for reference only, and the specific dimensions and weight of the genset after production completion shall prevail.



# **Engine Specifications**

Manufacturer	Yuchai
Model	YC6TD1000-D30
Engine output-prime	668kW
Engine output-standby	735kW
Frequency:	50Hz
Speed:	1500rpm
Cylinders no. & Type:	6 cylinders, Inline, 4 stroke, diesel engine,
	water-cooled
Aspiration:	Turbocharged&Intercooled
Bore*stroke	152*180mm
Displacement	19.60L
Compression Ratio	14:1
Governor	Electronic speed governor
Starter motor voltage:	24V DC
Type Injection System:	direct injection
Oil capacity(dry engine):	55L
Cooling way	Water Radiator & fan
Oil fuel ratio:	≤0.1%
Min fuel consumption rate	≤195 g/(kW·h)

- Heavy duty diesel engine
- Anti-vibration mount
- Replaceable fuel filter, oil filter & air filter
- Cooling radiator and fan

- Starter battery (with lead acid, free-maintenance)
- Flexible fuel connection hoses
- Exhaust silencer and bellows
- Operation manuals and circuit diagram documents

## **Alternator Specifications**

Alternator brand optional	Stamford/Leroy Somer/Marathon/ENGGA
Rated Voltage(V)	400/230
Output way	3 phase 4 wire
Rated power factor	0.8
Exciter	Brushless, Self-exciter
Wire connecting method	Y type, 3 phase 4 wire
Max voltage regulation	±1%
Protection class	IP23
Insulation class	Н
Rotor:	Single/double bearing
Efficiency:	95%
Regulator:	AVR
Recovery time(Tr)	1s
Waveform : TIF	<50
Waveform: THF	<2%
Overload	110% rated load for 2 hour per 24 hour



# **Control System**

Model:SmartGen HGM6110(optional Deep Sea)

**Origin: China** 

**Automatic controller** 



Operating Environment		
Operating temperature:	-25°C∼70°C	
Relative humidity:	95%	
Operating voltage:	DC24V(range: 8-35V)	

#### **Product Features:**

HGM6110 series automatic controller, integrating digital, intelligent and network techniques, is used for automatic control and monitoring system of genset. It can carry out functions of automatic start/stop, data measurement, alarm protection and three "remote" (remote control, remote measure and remote communication). The controller uses LCD display, optional display interface including Chinese, English, Spanish, Russian, Portuguese, Turkey, Polish and French with easy and reliable operation.

#### Below shut down causes are included:

- Low Coolant Level
- Low oil pressure
- High output frequency
- High output voltage
- Emergency stop

### High coolant temperature

- Low output frequency
- Low output voltage
- Low Fuel Level

### **Other Options**

☐ Oil heater	☐ Soundproof canopy genset
☐ Trailer genset	☐ Containerized type genset
☐ Coolant heater	☐ Automatic Parallel cabinet
☐ Starting batteries	☐ Fuel tank-Customizable capacity
☐ Automatic transfer switch (ATS)	☐ Heat exchangerWater-cooled tower system
☐ Spare parts	

#### Guangxi Dingbo Power Equipment Manufacturing Co., Ltd

Add: No. 10, Kechuang Road, High-tech Zone, Nanning, Guangxi, China

Tel: +86 13481024441 Fax: +86 771 5805 259

Web: www.dbdieselgenerator.com Email: dingbo@dieselgeneratortech.com